Appl. No. 10/750,499

Amdt. Dated August 21, 2006

Amendments to the Specification

Please replace paragraph [0004] of the specification with the following amended

paragraph:

Referring to Fig. 76, a conventional connector 200 comprises an insulative housing

210, a row of first contacts 224, two rows of second contacts 226, and two rows of third

contacts 228. The connector 200 are is connected to a circuit board 240 via the contacts 224,

226 and 228 being soldered to the circuit board 240. The insulative housing 210 integrally

forms a top wall 230, a bottom wall 232 and two side walls 234. However, the top wall 230,

bottom wall 232 and two side walls 234, which are used for guiding mating connectors and

protecting the contacts therein, complicate the configurations of the connector assembly.

Moreover, they complicate the injection mold toolings and process, which add costs to the

connector assembly or the hard disk drive. Furthermore, the extra processing of the additional

top, bottom and side walls wastes row raw materials and is not cost saving effective.

Please replace paragraph [0008] of the specification with the following amended

paragraph:

Other objects, advantages and novel features of the present invention will be drawn

from the following detailed description of preferred embodiments of the present invention with

and the attached accompanying drawings. , in which:

Please replace section title on page 3 of the specification with the following amended

section title:

3

Appl. No. 10/750,499 Amdt. Dated August 21, 2006

BRIEF DESCRIPTION OF THE DROWINGS DRAWINGS

Please replace the section title on page 4 of the specification with the following amended section title:

DETAILED DESCRIPTION OF THE INVENTION PREFERRED EMBODIMENT